

L3 ANSWER 144 OF 693 CA COPYRIGHT 2005 ACS on STN
 AN 137:113173 CA
 ED Entered STN: 15 Aug 2002
 TI Manufacture of semi-rigid asphalt concrete at ambient temperature
 IN Shen, De-Shian; Liu, Jeng-Tzung
 PA Taiwan
 SO Taiwan, 34 pp.
 CODEN: TWXXA5
 DT Patent
 LA Chinese
 IC ICM C04B024-36
 CC 58-2 (Cement, Concrete, and Related Building Materials)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	TW 408089	B	20001011	TW 1996-85116316	19961231
PRAI	TW 1996-85116316		19961231		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
TW 408089	ICM	C04B024-36

AB The concrete comprises Type-I cement 1, cation-emulsified asphalt 0.9-1.1, F-Type superplasticizer 0.03, Na CM-cellulose 0.09-0.11, CaCl₂ 0.01, fine sand/stone 0.933, coarse sand/stone 1.4 weight parts, and stone powder (as filler). Preferably, the F-Type superplasticizer is naphthalene type water reducing agent; and the Na CM-cellulose is water-dispersible polyanion. The concrete is manufactured by mixing the F-Type superplasticizer with the cation-emulsified asphalt, stirring, adding Na CM-cellulose, adding CaCl₂, adding surfactant, mixing, adding cement and stone powder, adding fine sand/stone, adding coarse sand/stone, and mixing. The concrete structure and construction machinery are also claimed.
 ST semi rigid asphalt concrete manuf ambient temp; sodium CM cellulose sand stone asphalt concrete; cement superplasticizer calcium chloride asphalt concrete; water reducing agent asphalt concrete